

SAFETY DATA SHEET

Date Issued : 3/26/2015

SDS No :SRG ISO

SRG Part B ISO

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: SRG Part B ISO**MANUFACTURER**

Metzger/McGuire Co.
PO BOX 2217
CONCORD, NH 03302-2217
PH: (800) 223-6680
FAX: (603) 224-6020
Email: info@metzgermcguire.com

24 HOUR EMERGENCY TELEPHONE NUMBERS

(800) 255-3924 24 hrs. (Continental U.S.)
(813) 248-0585 24 hrs. (Outside Continental U.S.)

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS

Health:

Acute Toxicity (Inhalation), Category 4
Skin Irritation, Category 2
Eye Irritation, Category 2
Respiratory Sensitization, Category 1
Skin Sensitization, Category 1
Target organ toxicity single exposure, Category 3
Target organ toxicity repeated exposure, Category 2

GHS LABEL



Health
hazard



Exclamation
mark

SIGNAL WORD: DANGER

HAZARD STATEMENTS

H315: Causes skin irritation.
H317: May cause an allergic skin reaction.
H319: Causes serious eye irritation.
H332: Harmful if inhaled.
H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335: May cause respiratory irritation.
H373: May cause damage to organs through prolonged or repeated exposure.

PRECAUTIONARY STATEMENT(S)

Prevention:

P260: Do not breathe mist, vapours or spray.
P264: Wash hands thoroughly after handling.
P271: Use only outdoors or in a well-ventilated area.
P280: Wear protective gloves, protective clothing, eye protection and face protection.
P284: In case of inadequate ventilation wear respiratory protection.

Response:

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P333+P313: If skin irritation or rash occurs: Get medical attention.

P304+P340: IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

P342+P311: If experiencing respiratory symptoms: Call a POISON CENTER or physician.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313: If eye irritation persists: Get medical attention.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS
Polymeric diphenylmethane diisocyanate	20 - 40	9016-87-9
4,4'-Diphenylmethane diisocyanate	20 - 40	101-68-8

4. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water. Remove contact lenses, if present. Seek medical attention if irritation persists.

SKIN: Immediately flush skin with water for at least 15 minutes. Remove contaminated clothing and shoes. Seek medical attention for severe exposure or if irritation persists.

INGESTION: Obtain immediate medical attention. Do not induce vomiting unless instructed to do so by poison center or physician.

INHALATION: Move person to fresh air. If breathing is difficult, oxygen should be administered by qualified personnel. If not breathing, give artificial respiration. Obtain medical attention. Symptoms can be delayed for several hours.

5. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: Water fog, foam, dry chemical or carbon dioxide.

HAZARDOUS COMBUSTION PRODUCTS: Carbon oxides, nitrogen oxides, isocyanates and trace amounts of hydrogen cyanide.

EXPLOSION HAZARDS: Water contamination produces carbon dioxide gas. This may cause pressurization or explosion of containers.

FIRE FIGHTING EQUIPMENT: Exposed firefighters must wear NIOSH-approved positive pressure self-contained breathing apparatus with full-face mask and full protective clothing.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Isolate the area and prevent entry of unnecessary and unprotected personnel. Do not walk through or otherwise scatter spilled product. Absorb with dry chemical absorbent, earth, sand or any other inert material. Place in a chemical waste container. Allow to stand uncovered 48 hours before closing container.

LARGE SPILL: Isolate the area and prevent entry of unnecessary and unprotected personnel. Do not walk through or otherwise scatter spilled product. Create a dike or trench to contain product. Prevent entry into waterways, sewers, basements or confined areas. Absorb with dry chemical absorbent, earth, sand or any other inert material. Place in a chemical waste container. Allow to stand uncovered 48 hours before closing container.

GENERAL PROCEDURES: Clean spill area with a decontamination solution. Suggested formulation: Sodium carbonate (5 - 10%), liquid detergent (1 - 2%), water (88 - 94%). Alternate formulation: Concentrated ammonia (3 - 8%), liquid detergent (1 - 2%), water (90 - 96%). Ensure adequate ventilation to prevent overexposure of ammonia.

SPECIAL PROTECTIVE EQUIPMENT: Wear protective equipment listed in Section 8.

7. HANDLING AND STORAGE

HANDLING: Do not get in eyes, on skin or on clothing. Wash hands before eating, drinking or smoking. Do not breathe vapors or mists. Use only with adequate ventilation. Keep container closed when not in use. Do not reseal if contaminated. Keep away from heat and flame.

STORAGE: Store in tightly closed containers in a cool, dry and well-ventilated area away from heat or sources of ignition. Keep out of direct sunlight.

STORAGE TEMPERATURE: 4.4°C (40°F) Minimum to 37.8°C (100°F) Maximum

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)					
		EXPOSURE LIMITS			
		OSHA PEL		ACGIH TLV	
Chemical Name		ppm	mg/m ³	ppm	mg/m ³
4,4'-Diphenylmethane diisocyanate	TWA	0.02 Ceiling	0.20 Ceiling	0.005	0.051

ENGINEERING CONTROLS: Local exhaust ventilation used in combination with general ventilation as necessary to control air contaminants.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Wear a face shield and chemical safety glasses or goggles.

SKIN: Wear impervious gloves. Cover exposed skin.

RESPIRATORY: For airborne exposure above the permissible exposure limit(s), wear a NIOSH approved air-purifying respirator equipped with organic vapor cartridges. For situations where the atmospheric levels may exceed the level for which an air-purifying respirator is effective, use a positive-pressure air-supplying respirator.

WORK HYGIENIC PRACTICES: Avoid eating, drinking or smoking while using this material. Wash hands thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

ODOR: Musty.

APPEARANCE: Amber liquid.

FLASH POINT AND METHOD: > 93.3°C (200°F) Closed cup.

AUTOIGNITION TEMPERATURE: > 300°C (572°F)

VAPOR PRESSURE: < 0.001 mmHg at 25°C (77°F)

VAPOR DENSITY: Heavier than air.

BOILING POINT: Not established.

FREEZING POINT: Not established.

SOLUBILITY IN WATER: Insoluble, reacts with water.

SPECIFIC GRAVITY: 1.15 (water = 1) at 23.3°C (74°F)

10. STABILITY AND REACTIVITY

STABILITY: Stable.

POLYMERIZATION: Can be caused by elevated temperatures.

CONDITIONS TO AVOID: Temperatures above 300 °F (148.9 °C).

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon oxides, nitrogen oxides, isocyanates and trace amounts of hydrogen cyanide.

INCOMPATIBLE MATERIALS: Amines, strong acids, strong bases, oxidizing agents and peroxides.

11. TOXICOLOGICAL INFORMATION

ACUTE

Chemical Name	ORAL LD ₅₀ (rat)	DERMAL LD ₅₀ (rabbit)	INHALATION LC ₅₀ (rat)
Polymeric diphenylmethane diisocyanate	> 10000 mg/kg	> 9400 mg/kg	310 mg/m ³ /4h
4,4'-Diphenylmethane diisocyanate	> 10000 mg/kg	> 9400 mg/kg	0.49 mg/L/4h (respirable aerosol)

CARCINOGENICITY

IARC: Not regulated as a carcinogen.

NTP: Not regulated as a carcinogen.

OSHA: Not regulated as a carcinogen.

SENSITIZATION: This material is a skin and respiratory sensitizer.

12. ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION: MDI: LC₅₀ (Brachydanio rerio) >500 mg/L/24h; EC₅₀ (Daphnia magna) 7060 mg/L/24h

BIOACCUMULATION/ACCUMULATION: In the aquatic and terrestrial environment, movement is expected to be limited by its reaction with water forming predominately insoluble polyureas.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Dispose in accordance with local, state, provincial or national regulations.

EMPTY CONTAINER: Decontaminate and pass to an approved drum recycler or destroy.

RCRA/EPA WASTE INFORMATION: If discarded in its purchased form, this material is not a RCRA hazardous waste.

GENERAL COMMENTS: The generation of waste should be avoided or minimized whenever possible. Chemical waste, even small quantities, should never be poured into drains, sewers or waterways.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: Not regulated when shipped below RQ.

AIR (ICAO/IATA)

SHIPPING NAME: Not regulated.

VESSEL (IMO/IMDG)

SHIPPING NAME: Not regulated.

15. REGULATORY INFORMATION**UNITED STATES****SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)**

311/312 HAZARD CATEGORIES: Acute, Chronic, Reactive.

EPCRA SECTION 313 SUPPLIER NOTIFICATION

Chemical Name	Wt.%	CAS	Comments
Polymeric diphenylmethane diisocyanate	20 - 40	9016-87-9	Diisocyanates category
4,4'-Diphenylmethane diisocyanate	20 - 40	101-68-8	Diisocyanates category

CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)

Chemical Name	Wt.%	CERCLA RQ
4,4'-Diphenylmethane diisocyanate	20 - 40	5000 lbs.

TSCA (TOXIC SUBSTANCE CONTROL ACT)

TSCA REGULATORY: All components are in TSCA inventory.

RCRA STATUS: If discarded in its purchased form, this material is not a RCRA hazardous waste.

NATIONAL RESPONSE CENTER: Any spill or release to the environment above the RQ must be reported to the National Response Center (800-424-8802).

16. OTHER INFORMATION

PREPARED BY: L. Priest

COMMENTS:

ACGIH	American Conference of Governmental Industrial Hygienists
CAS	Chemical Abstracts Service
EC ₅₀	Median effective concentration
EINECS	European Inventory of Existing Commercial Chemical Substances
GHS	Globally Harmonized System of Classification and Labeling of Chemicals
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
IMO	International Maritime Organization
LC ₅₀	Lethal concentration to 50% of exposed laboratory animals
LD ₅₀	Lethal dose to 50% of exposed laboratory animals
TWA	Time-weighted average
TLV	Threshold limit value
NIOSH	US National Institute of Occupational Safety and Health
NE	Not established
NTP	US National Toxicology Program
OEL	Occupational exposure limit
OSHA	US Occupational Safety Health Administration
PEL	Permissible exposure limit
RQ	Reportable quantity
STEL	Short term exposure limit

MANUFACTURER DISCLAIMER: The information in this SDS was obtained from sources that we believe are reliable. The

Information is provided without warranty, implied or expressed, concerning accuracy. The manufacturer assumes no legal responsibility for use or reliance on this information. This SDS is provided solely for the purpose of conveying health, safety and environmental information. This SDS is not a specification data sheet. Some of the information and conclusions may be derived from sources other than test data on the material itself.